

**MEASUREMENTS**

Mask (mm)	139 x 127 x 54 (L x W x H)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Nose cushion (mm)	139 x 127 x 1.5 (L x W x T)
Sup. elastic (mm)	300 x 5 x 0.55 (L x W x T)
Inf. elastic (mm)	265 x 5 x 0.55 (L x W x T)
Valve (mm)	41 x 11 (D x H)
Weight	18 g



**GENERAL DESCRIPTION AND MATERIALS**

- Single use mask **FFP2 NR D SL**
- Outer layer in **polypropylene**
- Inner layer in **polyester**
- Filter media : **High Filtration Efficiency Melt-Blown (polypropylene)**
- **Polypropylene and synthetic rubber** valve
- **Carbon** pre-filter against organic vapours
- **Aluminium** pince-nez
- Nose cushion in **foam polyethylene**
- Synthetic rubber elastic without latex

**SPECIFIC FEATURES**

- Allergic test
- Hygienic
- Expiration valve
- Against organic vapours
- Fire proof
- Waterproofness facial joint

**MAIN APPLICATION FIELDS**

- Protection against liquid and solid aerosols **up to 12xOEL**
- Against **organic vapours** under OEL
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls
- Against carbonate calcium, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hardwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)
- Do not use in a place where oxygen concentration is less than 17 Vol. %

**PACKING METHOD**

- **Individual** packing
- **120 masks** in a box
- 10 masks in an inner box

**CE STANDARDS**

This mask is in conformity with the model of individual safety equipment which complies with

• **The CE Type-examination certificate 593787**

Issued by **BSI (notified body n° 0086)**

This mask is in conformity with the  
« French JO notice » 135 dated  
06/12/04



**EN149 2001+A1 2009**