SINGLE USE MASK FFP2 NR D SL

VO-GA WITH VALVE

Ref. 23246

MEASUREMENTS	
MasK (mm)	139 x 127 x 54 (L x W x H)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Nose cushion (mm)	139 x 127 x 1.5 (L x W x T)
Sup. elastic (mm)	300 x 5 x 0.55 (L x W x T)
Inf. elastic (mm)	265 x 5 x 0.55 (L x W x T)
Valve (mm)	41 x 11 (D x H)
Weight	18 g



GENERAL DESCRIPTION AND MATERIALS

- Single use mask **FFP2 NR D SL**
- Outer layer in **polypropylene**
- Inner layer in **polyester**
- Filter media : **High Filtration Efficiency Melt-Blown (polypropylene)**
- **Polypropylene and synthetic rubber** valve
- **Carbon** pre-filter against organic vapours
- **Aluminium** pince-nez
- Nose cushion in **foam polyethylene**
- Synthetic rubber elastic without latex

SPECIFIC FEATURES

- Allergic test
- Hygienic
- Expiration valve
- Against organic vapours
- Fire proof
- Waterproofness facial joint

MAIN APPLICATION FIELDS

- Protection against liquid and solid aerosols **up to 12xOEL**
- Against **organic vapours** under OEL
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls
- Against carbonate calcium, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hardwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)
- Do not use in a place where oxygen concentration is less than 17 Vol. %

PACKING METHOD

- **Individual** packing
- **120 masks** in a box
- 10 masks in an inner box

CE STANDARDS

This mask is in conformity with the model of individual safety equipment which complies with

•The CE Type-examination certificate 593787

Issued by **BSI (notified body n° 0086)**

This mask is in conformity with the « French JO notice » 135 dated 06/12/04

CE

EN149 2001+A1 2009

P.O.Box 55228,3820 Limassol• Fax: 25390649 • Tel: 7777 1133 • E-mail:info@pngsafety.com • Web:www.pngsafety.com